

COSTAR PRIMER 10

Primer for Self-Levelling & Concrete Repair

Description

Costar Primer 10 is low-VOC, water-based solution used to prime surfaces prior to the application of self-leveling underlayment. It improves the performance and adhesion of self-leveling underlayment on nonporous and porous substrates.

Features

- Single-coat application for faster turnaround and lower installation costs
- Easy handling and application
- Enhances the performance and adhesion of underlayment on both porous and non-porous substrates

Areas of Use

- Interior residential (apartments, condominiums and homes)
- Interior commercial (office buildings, hotel rooms/hallways, restaurants and cafeterias)
- Interior heavy commercial (hotel lobbies, convention centers, airports, shopping malls, grocery stores and department stores)
- Interior institutional (hospitals, schools, universities, libraries and government buildings)

Application

■ Substrate Preparation

Adequate and detailed surface preparation is essential for durability of product after installation. Before application surface must be clean, dry and without contamination. The compressive strength of substrate must be at least 25MPa and cohesive bond strength must not be less than 1.5MPa.

Mixing and Application

Thoroughly shake the primer to agitate the contents, ensure all solids are distributed throughout the dispersion and a uniform consistency is achieved.

Apply Costar Primer 10 by brush or roller working the material into the prepared substrate. Typically, a single application is required; however, porous substrates may require two or more coats of primer to effectively seal the surface. Where multiple applications are necessary to seal the surface, allow previous coats to become tack-free before applying the second coat. Ponding of the substrate must be avoided and puddles must be removed.

To ensure proper adhesion, Costar Self-leveling Underlayment must be applied within 24hours of the application of the primer.

Coverage

- Approximately 2-3m² per liter

Packaging

- 20 liters Keg

COSTAR PRIMER 10



COSTAR PRIMER 10

Primer for Self-Levelling & Concrete Repair

Storage and Shelf Life

Costar Primer 10 has a shelf life of 12 months if kept in a dry store in the original, unopened.

Health & Safety

Costar Primer 10 should not be swallowed or allowed to come into contact with skin and eyes. Please use gloves and protective goggles. Avoid inhalation of dust. Wash skin contamination away with warm soapy water.

Limited Warranty

All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use away.

COSTAR PRIMER 10



Call Us:
+9254348314

E-mail Us
Info@costarchem.com

Office Address:
5041 Mountaire Area, Antioch, California, USA